

In the Claims

1. (Currently Amended) A liquid crystal display device ~~comprising~~ consisting essentially of:

- a back light assembly that generates a first light;
- a liquid crystal display panel including an upper substrate, a lower substrate facing the upper substrate, and a liquid crystal layer ~~interposes~~ interposed between the upper substrate and the lower substrate, the liquid crystal display panel receiving the first light generated from the back light assembly to display an image;
- a first polarizing plate disposed on the upper substrate;
- a selective reflection polarizing plate disposed on the first polarizing plate, the selective reflection polarizing plate ~~selectively~~ reflecting a portion of an external light; and
- a second polarizing plate disposed on the lower substrate.

2. (Original) The liquid crystal display device of claim 1, wherein the second polarizing plate polarizes the first light generated from the back light assembly, and the first polarizing plate analyzes a second light that passes through the liquid crystal display panel.

3. (Original) The liquid crystal display device of claim 1, wherein the selective reflection polarizing plate reflects a portion of the external light, the portion being above 50%.

4. (Original) The liquid crystal display device of claim 1, wherein the upper substrate includes color filters arranged in a matrix shape, and black matrix disposed between the color filters.

5. (Original) The liquid crystal display device of claim 4, wherein the black matrix comprises one selected from the group consisting of aluminum (Al), aluminum alloy, chromium (Cr), titanium (Ti), tantalum (Ta) and a mixture thereof.

6. (Currently Amended) The liquid crystal display device of claim 1, wherein a first polarizing axis of the first polarizing plate is substantially parallel with a polarizing axis ~~plate~~ of the selective reflection polarizing plate.

7. (Original) The liquid crystal display device of claim 1, wherein a first polarizing axis of the first polarizing plate is substantially perpendicular to a second polarizing axis of the second polarizing plate.

8. (Original) The liquid crystal display device of claim 1, wherein a first polarizing axis of the first polarizing plate is substantially parallel with a second polarizing axis of the second polarizing plate.

9. (Currently Amended) The liquid crystal display device of claim 1, wherein the selective reflection polarizing plate ~~film~~ corresponds to a linear selective reflection film.

10. (Currently Amended) The liquid crystal display device of claim 9, wherein the linear selective reflection polarizing plate ~~film~~ is a dual brightness enhancement film.

11. (Currently Amended) The liquid crystal display device of claim 1, wherein the selective reflection polarizing plate ~~film~~ corresponds to a circular selective reflection film.

12. (Original) The liquid crystal display device of claim 11, wherein the circular selective reflection film is a cholesteric liquid crystal polarizer.

13. (Currently Amended) A method of manufacturing a liquid crystal display device consisting essentially of comprising:

forming a liquid crystal display panel including an upper substrate, a lower substrate facing the upper substrate, and a liquid crystal layer interposes between the upper substrate and the lower substrate;

attaching a first polarizing plate on the upper substrate;

attaching a second polarizing plate on the lower substrate; and

attaching a selective reflection polarizing plate on the first polarizing plate, the selective reflection polarizing plate ~~selectively~~ reflecting a portion of an external light.

14. (Original) The method of claim 13, wherein the second polarizing plate polarizes a first light generated from the back light assembly, and the first polarizing plate analyzes a second light that passes through the liquid crystal display panel.

15. (Original) The method of claim 13, wherein the selective reflection polarizing plate reflects a portion of the external light, the portion being above 50%.

16. (Original) The method of claim 13, wherein the upper substrate includes color filters arranged in a matrix shape, and black matrix disposed between the color filters.

17. (Original) The method of claim 16, wherein the black matrix comprises one selected from the group consisting of aluminum (Al), aluminum alloy, chromium (Cr), titanium (Ti), tantalum (Ta) and a mixture thereof.

18. (Original) The method of claim 13, wherein a first polarizing axis of the first polarizing plate is substantially parallel with a polarizing plate of the selective reflection polarizing plate.

19. (Original) The method of claim 13, wherein a first polarizing axis of the first polarizing plate is substantially perpendicular to a second polarizing axis of the second polarizing plate.

20. (Original) The method of claim 13, wherein a first polarizing axis of the first polarizing plate is substantially parallel with a second polarizing axis of the second polarizing plate.

21. (Currently Amended) The method of claim 13, wherein the selective reflection polarizing plate ~~film~~ corresponds to a linear selective reflection film.

22. (Currently Amended) The method of claim 21, wherein the linear selective reflection polarizing plate film is a dual brightness enhancement film.

23. (Currently Amended) The method of claim 13, wherein the selective reflection polarizing plate film corresponds to a circular selective reflection film.

24. (Currently Amended) The method of claim 23, wherein the circular selective reflection polarizing plate film is a cholesteric liquid crystal polarizer.

25. (New) A liquid crystal display device comprising:
a back light assembly that generates a first light;
no more than one liquid crystal display panel, the liquid crystal display panel including an upper substrate, a lower substrate facing the upper substrate, and a liquid crystal layer interposed between the upper substrate and the lower substrate, the liquid crystal display panel receiving the first light generated from the back light assembly to display an image;
a first polarizing plate disposed on the upper substrate;
a selective reflection polarizing plate disposed on the first polarizing plate, the selective reflection polarizing plate reflecting a portion of an external light; and
a second polarizing plate disposed on the lower substrate.